# Safety Data Sheet acc. to OSHA HCS

Printing date 02/28/2023

\*

\*

Reviewed on 02/28/2023

Identification	
· Product identifier	
· Trade name: Ethanol undenaturated absolute	CFD1/A
Article number: 11093	
CAS Number:	
64-17-5	
· EC number:	
200-578-6	
· Index number:	
603-002-00-5	
• Application of the substance / the mixture: Laboratory chemicals	$(\Delta)$
• Details of the supplier of the safety data sheet	<u> </u>
· Manufacturer/Supplier:	
SERVA Electrophoresis GmbH	0
Carl-Benz-Str. 7	
D-69115 Heidelberg	
Tel.: +49 6221 13840-0 FAX: +49 6221 13840-10	
msds.info@serva.de	
	25
Information department: Product Safety department Tel.: +49 6221 13840	-35
Emergency telephone number: Medical Emergency Information in case of poisoning	
Medical Emergency Information in case of poisoning: Poison Information Center Mainz - Phone: +49 (0) 6131 19240	
(advisory service in German or English language)	
(auvisory service in German or English tangaage)	
C M	
Hazard(s) identification	
Classification of the substance or mixture	
GHS02	
Flammable Liquids 2 H225 Highly flammable liquid and vapor.	
Flammable Liquids 2 H225 Highly flammable liquid and vapor.	
Flammable Liquids 2 H225 Highly flammable liquid and vapor.	
GHS07	
<i>GHS07</i> <i>Eye Irritation 2A H319 Causes serious eye irritation.</i>	
<i>GHS07</i> <i>Eye Irritation 2A H319 Causes serious eye irritation.</i> <i>Label elements</i>	
<i>GHS07</i> <i>Eye Irritation 2A H319 Causes serious eye irritation.</i> <i>Label elements</i> <i>GHS label elements</i>	
<i>Eye Irritation 2A</i> H319 Causes serious eye irritation. <i>Label elements</i> <i>GHS label elements</i> <i>The substance is classified and labeled according to the Globally Harmoniz</i>	zed System (GHS).
GHS07         Eye Irritation 2A       H319 Causes serious eye irritation.         Label elements         GHS label elements         The substance is classified and labeled according to the Globally Harmoniz         Hazard pictograms: GHS02, GHS07	zed System (GHS).
Eye Irritation 2A       H319 Causes serious eye irritation.         Label elements       GHS label elements         The substance is classified and labeled according to the Globally Harmoniz         Hazard pictograms: GHS02, GHS07         Signal word: Danger	zed System (GHS).
Eye Irritation 2A       H319 Causes serious eye irritation.         Eye Irritation 2A       H319 Causes serious eye irritation.         Label elements       GHS label elements         The substance is classified and labeled according to the Globally Harmoniz         Hazard pictograms: GHS02, GHS07         Signal word: Danger         Hazard statements:	zed System (GHS).
Eye Irritation 2A       H319 Causes serious eye irritation.         Label elements       H319 Causes serious eye irritation.         Label elements       H319 Causes serious eye irritation.         Habel elements       H319 Causes serious eye irritation.         Habel elements       H319 Causes serious eye irritation.         Habel elements       H319 Causes serious eye irritation.         Haster elements:       H319 Causes serious eye irritation.         Haster elements:       Haster elements:         Highly flammable liquid and vapor.	zed System (GHS).
Eye Irritation 2A       H319 Causes serious eye irritation.         Label elements       H319 Causes serious eye irritation.         GHS label elements       The substance is classified and labeled according to the Globally Harmoniz         Hazard pictograms: GHS02, GHS07       Signal word: Danger         Hazard statements:       Highly flammable liquid and vapor.         Causes serious eye irritation.       Causes serious eye irritation.	zed System (GHS).
Eye Irritation 2A H319 Causes serious eye irritation. Label elements GHS label elements The substance is classified and labeled according to the Globally Harmoniz Hazard pictograms: GHS02, GHS07 Signal word: Danger Hazard statements: Highly flammable liquid and vapor. Causes serious eye irritation.	zed System (GHS).
Eye Irritation 2A       H319 Causes serious eye irritation.         Label elements       H319 Causes serious eye irritation.         Label elements       H319 Causes serious eye irritation.         Hazard statements:       H319 Causes serious eye irritation.         Hazard statements:       H319 Causes serious eye irritation.         Highly flammable liquid and vapor.       Causes serious eye irritation.         Precautionary statements       Hazard statements	zed System (GHS).
Eye IrritationEye Irritation 2AH319 Causes serious eye irritation.Label elementsGHS label elementsThe substance is classified and labeled according to the Globally HarmonizHazard pictograms: GHS02, GHS07Signal word: DangerHazard statements:Highly flammable liquid and vapor.Causes serious eye irritation.Precautionary statementsKeep away from heat/sparks/open flames/hot surfaces No smoking.	zed System (GHS).
Eye IrritationEye Irritation 2AH319 Causes serious eye irritation.Label elementsGHS label elementsThe substance is classified and labeled according to the Globally HarmonizHazard pictograms: GHS02, GHS07Signal word: DangerHazard statements:Highly flammable liquid and vapor.Causes serious eye irritation.Precautionary statementsKeep away from heat/sparks/open flames/hot surfaces No smoking.Take precautionary measures against static discharge.	zed System (GHS).
Eye IrritationEye Irritation 2AH319 Causes serious eye irritation.Label elementsGHS label elementsThe substance is classified and labeled according to the Globally HarmonizHazard pictograms: GHS02, GHS07Signal word: DangerHazard statements:Highly flammable liquid and vapor.Causes serious eye irritation.Precautionary statementsKeep away from heat/sparks/open flames/hot surfaces No smoking.Take precautionary measures against static discharge.Wash thoroughly after handling.Wear protective gloves/protective clothing/eye protection/face protection.If on skin (or hair): Take off immediately all contaminated clothing. Rinse state	skin with water/shower.
Eye IrritationEye Irritation 2AH319 Causes serious eye irritation.Label elementsGHS01GHS02Bignal word: classified and labeled according to the Globally Harmonia:Hazard pictograms: GHS02, GHS07Signal word: DangerHazard statements:Highly flammable liquid and vapor.Causes serious eye irritation.Precautionary statementsKeep away from heat/sparks/open flames/hot surfaces No smoking.Take precautionary measures against static discharge.Wash thoroughly after handling.Wear protective gloves/protective clothing/eye protection/face protection.If on skin (or hair): Take off immediately all contaminated clothing. Rinse sIf in eyes: Rinse cautiously with water for several minutes. Remove contact	skin with water/shower.
Eye IrritationEye Irritation 2AH319 Causes serious eye irritation.Label elementsGHS01GHS02GHS02, GHS07Signal word: DangerHazard pictograms: GHS02, GHS07Signal word: DangerHazard statements:Highly flammable liquid and vapor.Causes serious eye irritation.Precautionary statementsKeep away from heat/sparks/open flames/hot surfaces No smoking.Take precautionary measures against static discharge.Wash thoroughly after handling.Wear protective gloves/protective clothing/eye protection/face protection.If on skin (or hair): Take off immediately all contaminated clothing. Rinse state	skin with water/shower.

Printing date 02/28/2023

Reviewed on 02/28/2023


#### Trade name: Ethanol undenaturated absolute

Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international regulations. • Classification system:

• NFPA ratings (scale 0 - 4)

4 + 4 = 2 4 + 4 = 2 7 + 4 = 3 7 +





- · Other hazards
- · Results of PBT and vPvB assessment:

• **PBT:** PBT - assessment not available.

· **vPvB**: vPvB - assessment not available.

#### 3 Composition/information on ingredients

- · Chemical characterization: Substances
- CAS No. Description: 64-17-5 ethanol
- Identification number(s):
- **EC number:** 200-578-6
- Index number: 603-002-00-5
- · Description:
- Empirical formula:  $C_2 H_6 O$
- · MŴ: 46.1

## 4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact:
- Immediately wash with water and soap and rinse thoroughly. Consult doctor if you feel unwell.
- · After eye contact:

Rinse opened eye for several minutes under running water. Remove present contact lenses, if easy to do, and continue rinsing. Consult ophthalmologist In case of complaints.

- *After swallowing:* Wash out mouth. Drink plenty of water and supply fresh air. Seek medical advice if discomfort occurs. Do not induce vomiting!
- · Most important symptoms and effects, both acute and delayed Dizziness
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

## **5** Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- $CO_{2}$  extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. • Special hazards arising from the substance or mixture
- Vapours can form flammable and explosive mixtures with air. Vapours are heavier than air and spread over the floor. Accumulation in low areas is possible.
- Formation of toxic gases is possible during heating or in case of fire.

(Contd. on page 3)

US

(Contd. of page 1)

(Contd. of page 2)

# Safety Data Sheet acc. to OSHA HCS

Printing date 02/28/2023

Reviewed on 02/28/2023

#### Trade name: Ethanol undenaturated absolute

In case of fire, the following can be released:

Carbon monoxide and carbon dioxide

• Advice for firefighters

· Protective equipment: Wear self-contained respiratory protective device.

## 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures Wear protective clothing. Ensure adequate ventilation Particular danger of slipping on leaked/spilled product.
Environmental precautions: Prevent seepage into sewage system, workpits and cellars. Do not allow to enter sewers/ surface or ground water.
Methods and material for containment and cleaning up Dispose contaminated material as waste according to item 13. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Protective Action Criteria for Chemicals

• PAC-1: 1,800 ppm

· PAC-2: 3300\* ppm

- · PAC-3: 15000\* ppm
- Reference to other sections
   See Section 7 for information on safe handling.
   See Section 8 for information on personal protection equipment.
   See Section 13 for disposal information.

#### 7 Handling and storage

- · Precautions for safe handling: Keep receptacles tightly sealed.
- Information about protection against explosions and fires: Protect against electrostatic charges. Keep ignition sources away - Do not smoke.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- *Requirements to be met by storerooms and receptacles:* Store only in the original receptacle. Unsuitable material for receptacle: aluminium. Store in a cool location.
- Information about storage in one common storage facility: Store away from oxidizing agents.
- Further information about storage conditions: Store containers in a dry and well-ventilated place. Keep receptacle tightly sealed.
- Specific end use(s): No further relevant information available.

#### 8 Exposure controls/personal protection

· Control parameters

· Components with limit values that require monitoring at the workplace:

64-17-5 ethanol (80-100%)

PEL Long-term value: 1900 mg/m<sup>3</sup>, 1000 ppm

REL Long-term value: 1900 mg/m<sup>3</sup>, 1000 ppm

TLV Short-term value: 1000 ppm

A3

(Contd. on page 4)

US

Printing date 02/28/2023

\*

Reviewed on 02/28/2023

Additional information: The lists that were va Exposure controls Additional information about design of techn Personal protective equipment:	(Contd. of page 3
Exposure controls Additional information about design of techn Personal protective equipment:	
Additional information about design of techn Personal protective equipment:	ila during the creation were used as basis.
Personal protective equipment:	
	ical systems: No further data; see item 7.
Con anal must a stir a set I have it is the set	
General protective and hygienic measures:	
Keep away from foodstuffs, beverages and feed	1.
Store protective clothing separately.	ad alashing
Immediately remove all soiled and contaminat Avoid contact with the eyes and skin.	ea cioining.
Wash hands before breaks and at the end of we	ork
Avoid contact with the eyes.	<i></i>
Breathing equipment:	
Short term filter device:	
Filter A/P2	
Protection of hands:	
	resistant to the product/ the substance/ the preparation.
	e glove material can be given for the product/ the preparation
the chemical mixture.	
	ration of the penetration times, rates of diffusion and th
degradation Material of gloves:	
	t only depend on the material, but also on further marks o
quality and varies from manufacturer to manuf	
Penetration time of glove material:	
	put by the manufacturer of the protective gloves and has to b
observed.	
For the permanent contact of a maximum	of 15 minutes gloves made of the following materials are
suitable:	
Nitrile rubber, NBR	
Butyl rubber, BR	
Chloroprene rubber, CR Eye protection: Tightly sealed goggles	
<b>Body protection:</b> Protective work clothing	
2009 Protection	
Physical and chemical properties	
Information on basic physical and chemical p General Information:	properties
Color:	Colorless
Odor:	Characteristic
01 1 1 11	Not determined.
Odor threshold:	-114 °C (-173.2 °F)
Odor threshold: Melting point/Melting range:	-114 C (-1/3.2 r)
Melting point/Melting range: Boiling point/Boiling range:	78 °C (172.4 °F)
Melting point/Melting range: Boiling point/Boiling range: Flammability (solid, gaseous):	
Melting point/Melting range: Boiling point/Boiling range: Flammability (solid, gaseous): Explosion limits:	78 °C (172.4 °F) Highly flammable.
Melting point/Melting range: Boiling point/Boiling range: Flammability (solid, gaseous): Explosion limits: Lower:	78 °C (172.4 °F) Highly flammable. 3.4 Vol %
Melting point/Melting range: Boiling point/Boiling range: Flammability (solid, gaseous): Explosion limits: Lower: Upper:	78 °C (172.4 °F) Highly flammable. 3.4 Vol % 15 Vol %
Melting point/Melting range: Boiling point/Boiling range: Flammability (solid, gaseous): Explosion limits: Lower: Upper: Flash point:	78 °C (172.4 °F) Highly flammable. 3.4 Vol % 15 Vol % 12 °C (53.6 °F)
Melting point/Melting range: Boiling point/Boiling range: Flammability (solid, gaseous): Explosion limits: Lower: Upper: Flash point: Ignition temperature:	78 °C (172.4 °F) Highly flammable. 3.4 Vol % 15 Vol % 12 °C (53.6 °F) 425 °C (797 °F)
Melting point/Melting range: Boiling point/Boiling range: Flammability (solid, gaseous): Explosion limits: Lower: Upper: Flash point: Ignition temperature: Decomposition temperature:	78 °C (172.4 °F) Highly flammable. 3.4 Vol % 15 Vol % 12 °C (53.6 °F) 425 °C (797 °F) no information available
Melting point/Melting range: Boiling point/Boiling range: Flammability (solid, gaseous): Explosion limits: Lower: Upper: Flash point: Ignition temperature: Decomposition temperature: pH-value:	78 °C (172.4 °F) Highly flammable. 3.4 Vol % 15 Vol % 12 °C (53.6 °F) 425 °C (797 °F)
Melting point/Melting range: Boiling point/Boiling range: Flammability (solid, gaseous): Explosion limits: Lower: Upper: Flash point: Ignition temperature: Decomposition temperature: pH-value: Viscosity:	78 °C (172.4 °F) Highly flammable. 3.4 Vol % 15 Vol % 12 °C (53.6 °F) 425 °C (797 °F) no information available Not determined.
Melting point/Melting range: Boiling point/Boiling range: Flammability (solid, gaseous): Explosion limits: Lower: Upper: Flash point: Ignition temperature: Decomposition temperature: pH-value:	78 °C (172.4 °F) Highly flammable. 3.4 Vol % 15 Vol % 12 °C (53.6 °F) 425 °C (797 °F) no information available

Printing date 02/28/2023

Reviewed on 02/28/2023

#### Trade name: Ethanol undenaturated absolute

	(Contd. of page 4
· Solubility in / Miscibility with:	
· Water:	Fully miscible.
· Partition coefficient (n-octanol/water):	no information available
· Vapor pressure at 20 °C (68 °F):	59 hPa (44.3 mm Hg)
• Density at 20 •C (68 •F):	0.79 g/cm <sup>3</sup> (6.59255 lbs/gal)
· Relative density:	no information available
· Other information	There are no more data available.
· Appearance:	
· Form:	Fluid
• Important information on protection of health and environment, and on safety:	
· Danger of explosion:	Product is not explosive. However, formation o explosive air/vapor mixtures are possible.
· Molecular weight	46.1 g/mol

### **10 Stability and reactivity**

- · Reactivity: No further relevant information available.
- · Chemical stability:
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions: Vapours can form flammable and explosive mixtures with air.
- · Conditions to avoid:

Avoid high temperatures, flames, sparks static discharge

- · Incompatible materials:
- Avoid contact with:

Oxidizers

alkaline earth metals, peroxides, phosphorus oxides, nitrogen oxides, perchlorates, chrome oxides, hydrogen peroxide, nitric (V) acid, sulfuric (VI) acid, acid chlorides

• Hazardous decomposition products: In case of fire: See Section 5

## **11 Toxicological information**

- · Information on toxicological effects
- Acute toxicity: Based on available data, the classification criteria are not met.

## · LD/LC50 values that are relevant for classification:

Oral	LD50	10,470 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LC50/4h	124.7 mg/l (rat)

- on the eye: Causes serious eye irritation.
- · Additional toxicological information:
- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer) 1
- · NTP (National Toxicology Program) Substance is not listed.
- · OSHA-Ca (Occupational Safety & Health Administration) Substance is not listed.

### **12** Ecological information

- · Toxicity:
- Aquatic toxicity:
- LC50/96h (Oncorhynchus mykiss): 13000 mg/l

LC50/48h (Daphnia magna): 12340 mg/l

(Contd. on page 6)

US

Printing date 02/28/2023

Reviewed on 02/28/2023

## Trade name: Ethanol undenaturated absolute

(Contd. of page 5)

Toxicity to algae: NOEC (Lemi	na gibba, $OECD \ 201) = 280 \ mg/l$
· Persistence and degradability:	Easily biodegradable
• Other information:	
OECD 301 B (ready biodegrad	lability/ CO2 evolution test)
Biodegradation:	
97 %	
· Bioaccumulative potential: BC	CF: 0,66 - 3,2 mg/l
• Mobility in soil: No further rel	evant information available.
· Results of PBT and vPvB asse	ssment:
• <b>PBT:</b> Not applicable.	
• <b>vPvB:</b> Not applicable.	
• Other adverse effects:	
· Remark:	
LC50 / 48 h (Leuciscus idus):	8140 mg / l
LC50 / 96 h (Copepoda): 6500	mg/l
Additional ecological information	tion:
General notes:	
Do not allow product to reach	ground water, water course or sewage system.
	ent by list): slightly hazardous for water

# **13 Disposal considerations**

#### · Waste treatment methods

· Recommendation:

Disposal must be made according to official regulations. Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

• *Recommendation:* Disposal of uncleaned packagings must be made according to official regulations in the same manner as the product.

· Recommended cleansing agent: Water, if necessary with cleansing agents.

· UN-Number		
· DOT, ADR, IMDG, IATA	UN1170	
· UN proper shipping name		
·DOT	Ethanol	
· ADR	1170 ETHANOL (ETHYL ALCOHOL)	
·IMDG	ETHANOL (ETHYL ALCOHOL)	
·IATA	ETHANOL	
· Transport hazard class(es)		
·DOT		
RAMARE LON		
3		

Printing date 02/28/2023

Reviewed on 02/28/2023

## Trade name: Ethanol undenaturated absolute

	(Contd. of pag
Label	3
ADR, IMDG, IATA	
Class:	3 Flammable liquids
Label:	3
Packing group DOT, ADR, IMDG, IATA	Ш
Environmental hazards	Not applicable.
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code):	
EMS Number:	F-E,S-D
Stowage Category	A
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1170 ETHANOL (ETHYL ALCOHOL), 3, II

# **15 Regulatory information**

• Safety, health and environmental regulations/legislation specific for the substance or mixture • Section 355 (extremely hazardous substances): Substance is not listed.

- Section 313 (Specific toxic chemical listings): Substance is not listed.
- TSCA (Toxic Substances Control Act): ACTIVE
- Hazardous Air Pollutants Substance is not listed.
- **Proposition 65** Substance is not listed.
- · Chemicals known to cause cancer: Substance is not listed.
- · Chemicals known to cause reproductive toxicity for females: Substance is not listed.
- · Chemicals known to cause reproductive toxicity for males: Substance is not listed.
- · Chemicals known to cause developmental toxicity: Substance is listed.
- · Cancerogenity categories
- · EPA (Environmental Protection Agency) Substance is not listed.
- TLV (Threshold Limit Value) A3
- · NIOSH-Ca (National Institute for Occupational Safety and Health) Substance is not listed.
- · GHS label elements
- *The substance is classified and labeled according to the Globally Harmonized System (GHS). Hazard pictograms* GHS02, GHS07
- · Signal word Danger

(Contd. on page 8)

Printing date 02/28/2023

Reviewed on 02/28/2023

#### Trade name: Ethanol undenaturated absolute

(Contd. of page 7) · Hazard statements *Highly flammable liquid and vapor.* Causes serious eye irritation. · Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Take precautionary measures against static discharge. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Store in a well-ventilated place. Keep cool. Dispose of contents/container in accordance with local/regional/national/international regulations. · National regulations: • Information about limitation of use: Employment restrictions concerning young persons must be observed. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out. **16** Other information This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. · Department issuing SDS: Product safety department · Contact: +49 6221 13840-35 · Date of preparation / last revision 02/28/2023 · Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation PBT: persistent, bioaccumulative, toxic substance (REACH) vPvB: very persistent, very bioaccumulative substance (REACH) REACH: Regulation concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals CLP: Regulation on classification, labelling and packaging of substances and mixtures bw: body weight ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flammable Liquids 2: Flammable liquids – Category 2 Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A