

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/03/2018

Reviewed on 05/03/2018

1 Identification

- **Product identifier**
- **Trade name:** Silicone solution SERVA
for siliconizing glass and metal
- **Article number:** 35130
- **Application of the substance / the mixture** Laboratory chemicals
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SERVA Electrophoresis GmbH
Carl-Benz-Str. 7
D-69115 Heidelberg
Tel.: +49 6221 13840-0
FAX: +49 6221 13840-10
msds.info@serva.de
- **Information department:** Product Safety department Tel.: +49 6221 13840-35
- **Emergency telephone number:**
Medical Emergency Information in case of poisoning:
Poison Information Center Mainz - Phone: +49 (0) 6131 19240
(advisory service in German or English language)



2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms** GHS02, GHS07
- **Signal word** Danger
- **Hazard-determining components of labeling:**
propan-2-ol
- **Hazard statements**
Highly flammable liquid and vapor.
Causes serious eye irritation.
May cause drowsiness or dizziness.
- **Precautionary statements**
Keep away from heat/sparks/open flames/hot surfaces. No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Avoid breathing dust/fume/gas/mist/vapors/spray
Wash thoroughly after handling.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/03/2018

Reviewed on 05/03/2018

Trade name: Silicone solution SERVA
for silicizing glass and metal

(Contd. of page 1)

Use only outdoors or in a well-ventilated area.

Wear protective gloves / eye protection / face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a POISON CENTER/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO₂, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 1

Fire = 3

Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** PBT - assessment not available.

· **vPvB:** vPvB - assessment not available.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

67-63-0	propan-2-ol	80-100%
---------	-------------	---------

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· **Description of first aid measures**

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly. Consult doctor if you feel unwell.

· **After eye contact:**

Rinse opened eye for several minutes under running water. Remove present contact lenses, if easy to do, and continue rinsing. Consult ophthalmologist In case of complaints.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed**

Dizziness

Headache

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/03/2018

Reviewed on 05/03/2018

Trade name: Silicone solution SERVA
for siliconizing glass and metal

(Contd. of page 2)

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

*

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂ extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture**
Flammable substance, vapours are heavier than air and spread over the floor.
Vapours can form flammable and explosive mixtures with air.
Formation of dangerous gases or vapours is possible in case of fire.
In case of fire, the following can be released:
Carbon monoxide and carbon dioxide
- **Advice for firefighters**
- **Protective equipment:** Wear self-contained respiratory protective device.

*

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective clothing.
Ensure adequate ventilation
Avoid contact with the eyes and skin.
Do not inhale vapours.
Keep away from ignition sources
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

*

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Keep receptacles tightly sealed.
Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.
- **Information about storage in one common storage facility:** Do not store together with oxidizing materials.
- **Further information about storage conditions:** Keep receptacle tightly sealed and store in dry conditions.
- **Specific end use(s)** No further relevant information available.

*

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/03/2018

Reviewed on 05/03/2018

Trade name: Silicone solution SERVA
for silicizing glass and metal

(Contd. of page 3)

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

67-63-0 propan-2-ol (80-100%)

PEL	Long-term value: 980 mg/m ³ , 400 ppm
REL	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV	Short-term value: 984 mg/m ³ , 400 ppm Long-term value: 492 mg/m ³ , 200 ppm
BEI	

· **Ingredients with biological limit values:**

67-63-0 propan-2-ol (80-100%)

BEI	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
-----	---

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Store protective clothing separately.

Immediately remove all soiled and contaminated clothing.

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

Wash hands before breaks and at the end of work.

· **Breathing equipment:**

Short term filter device:

Filter A/P2

· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Nitrile rubber, NBR

Chloroprene rubber, CR

· **Eye protection:** Tightly sealed goggles

· **Body protection:** Protective work clothing

US

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/03/2018

Reviewed on 05/03/2018

Trade name: Silicone solution SERVA
for silicizing glass and metal

(Contd. of page 4)

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Liquid
Color:	Colorless
Odor:	Characteristic

· pH-value (- g/l) at 20 °C (68 °F): neutral

· Change in condition

Melting point/Melting range:	-88 °C (-126 °F)
Boiling point/Boiling range:	82 °C (180 °F)

· Flash point: 13 °C (55 °F)

· Ignition temperature: 425 °C (797 °F)

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower:	2 Vol %
Upper:	13.4 Vol %

· Vapor pressure at 20 °C (68 °F): 43 hPa (32 mm Hg)

· Density at 20 °C (68 °F): 0.785 g/cm³ (6.551 lbs/gal)

· Solubility in / Miscibility with

Water: Fully miscible.

· Solvent content:

Organic solvents:	97.0 %
VOC content:	97.0 %

Solids content: 3.0 %

· Other information The physico-chemical data correspond to absolute propan-2-ol.

10 Stability and reactivity

· Reactivity No further relevant information available.

· Chemical stability

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· Possibility of hazardous reactions

Vapours can form flammable and explosive mixtures with air.

Reacts with strong oxidizing agents.

Used empty containers may contain product gases which form explosive mixtures with air.

Danger of bursting.

· Conditions to avoid high temperatures

· Incompatible materials:

Avoid contact with:

rubber and several plastic materials

Strong oxidizers

Strong acids

· Hazardous decomposition products: In case of fire: See Section 5

US

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/03/2018

Reviewed on 05/03/2018

Trade name: Silicone solution SERVA
for siliconizing glass and metal

(Contd. of page 5)

11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12800 mg/kg (rabbit)
Inhalative	LC50/4h	30 mg/l (rat)
	LC50/96h	9640 mg/l (Forelle)

- **Primary irritant effect:**

- **on the eye:** Irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

67-63-0	propan-2-ol	3
---------	-------------	---

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:**

EC50/48h	13299 mg/l (Daphnia magna)
EC50/72h	> 1000 mg/l (Scenedesmus subspicatus)

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow product to reach ground water, water course or sewage system.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

(Contd. on page 7)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/03/2018



Reviewed on 05/03/2018

Trade name: Silicone solution SERVA
for siliconizing glass and metal

(Contd. of page 6)

- **Uncleaned packagings:**
- **Recommendation:**
Disposal of uncleaned packagings must be made according to official regulations in the same manner as the product.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

- | | |
|---|---|
| · UN-Number | UN1219 |
| · DOT, ADR, IMDG, IATA | |
| · UN proper shipping name | 1219 ISOPROPANOL (ISOPROPYL ALCOHOL) |
| · ADR | ISOPROPANOL (ISOPROPYL ALCOHOL) |
| · IMDG | Isopropanol |
| · IATA | |
| · Transport hazard class(es) | |
| · DOT | |
|  | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · ADR, IMDG, IATA | |
|  | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · Packing group | II |
| · DOT, ADR, IMDG, IATA | |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Warning: Flammable liquids |
| · Danger code (Kemler): | 33 |
| · EMS Number: | F-E,S-D |
| · Stowage Category | B |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · ADR | |
| · Excepted quantities (EQ) | Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml |
| · IMDG | |
| · Limited quantities (LQ) | 1L |

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/03/2018

Reviewed on 05/03/2018

Trade name: Silicone solution SERVA
for siliconizing glass and metal

(Contd. of page 7)

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":**

UN1219, ISOPROPANOL (ISOPROPYL ALCOHOL), 3, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

All ingredients are listed.

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

None of the ingredients is listed.

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenicity categories**· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

67-63-0 propan-2-ol

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms** GHS02, GHS07· **Signal word** Danger· **Hazard-determining components of labeling:**

propan-2-ol

· **Hazard statements**

Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause drowsiness or dizziness.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/03/2018

Reviewed on 05/03/2018

Trade name: Silicone solution SERVA
for siliconizing glass and metal

(Contd. of page 8)

Avoid breathing dust/fume/gas/mist/vapors/spray
 Wash thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves / eye protection / face protection.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
 Continue rinsing.
 Call a POISON CENTER/doctor if you feel unwell.
 If eye irritation persists: Get medical advice/attention.
 In case of fire: Use for extinction: CO₂, powder or water spray.
 Store in a well-ventilated place. Keep container tightly closed.
 Store in a well-ventilated place. Keep cool.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.
 • **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Product safety department
- **Contact:** +49 6221 13840-35
- **Date of preparation / last revision** 05/03/2018 / 6
- **Abbreviations and acronyms:**
 - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 - ICAO: International Civil Aviation Organisation
 - PBT: persistent, bioaccumulative, toxic substance (REACH)
 - vPvB: very persistent, very bioaccumulative substance (REACH)
 - REACH: Regulation concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals
 - CLP: Regulation on classification, labelling and packaging of substances and mixtures
 - ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - DOT: US Department of Transportation
 - IATA: International Air Transport Association
 - ACGIH: American Conference of Governmental Industrial Hygienists
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - NFPA: National Fire Protection Association (USA)
 - HMIS: Hazardous Materials Identification System (USA)
 - VOC: Volatile Organic Compounds (USA, EU)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - NIOSH: National Institute for Occupational Safety
 - OSHA: Occupational Safety & Health
 - TLV: Threshold Limit Value
 - PEL: Permissible Exposure Limit
 - REL: Recommended Exposure Limit
 - BEI: Biological Exposure Limit
 - Flam. Liq. 2: Flammable liquids – Category 2
 - Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
 - STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- *** Data compared to the previous version altered.**