

**A N A L Y S E N Z E R T I F I K A T**  
 CERTIFICATE OF ANALYSIS

<b>Xylan aus Buchenholz rein</b> Xylan from beech wood pure	<b>Kat.Nr./Cat.No. : 38500</b> <b>Lot/Contr.No. : 201130</b>
--	---

<b>Parameter</b> parameter	<b>Methode</b> method	<b>Spezifikation</b> specification	<b>Ergebnis</b> result
<b>Aussehen</b> appearance		beiges Pulver beige powder	entspricht corresponds
<b>Trocknungsverlust (%)</b> loss on drying	3 h, 110 °C	max. 5.0	2.7
<b>[α]D/ 20 °C</b>	1% in 5% NaOH	-75.0° bis/ to -65.0°	-67°
<b>Mindesthaltbarkeit</b> minimum shelf life			21.10.2025
<b>Lagerung (°C)</b> storage			+15 bis/ to +30

**Die Eignung des Produktes für spezielle Anwendungszwecke wird nicht zugesichert.**  
**Dieses Dokument entbindet nicht von einer branchenüblichen Eingangskontrolle.**  
 We do not guarantee that the product can be used for a special application.  
 This document does not release you from performing the standard control upon receipt of incoming goods.

**SERVA Electrophoresis GmbH**  
**Qualitätskontrolle/ Quality Control**

**Druckdatum/ printing date: 22.10.2020**

Christian Monsler

Daniela Lux-Helmstetter

**Dieses Dokument ist ein Computerausdruck und deshalb ohne Unterschrift gültig.**  
 This report has been computer generated and does not contain a signature.