

ANALYSENZERTIFIKAT
CERTIFICATE OF ANALYSIS

Xylan aus Buchenholz rein	Kat.Nr./Cat.No. :	38500
Xylan from beech wood pure	Lot/Contr.No. :	230685

Parameter parameter	Methode method	Spezifikation specification	Ergebnis result
Aussehen appearance		beiges Pulver beige powder	entspricht corresponds
Trocknungsverlust (%) loss on drying	3 h, 110 °C	max. 5.0	2.9
[α]_D/ 20 °C	1% in 5% NaOH	-75.0° bis/ to -65.0°	-68°
Mindesthaltbarkeit minimum shelf life			15.06.2028
Lagerung (°C) storage			+15 bis/ to +30

Die Eignung des Produktes für spezielle Anwendungszwecke wird nicht zugesichert.
Dieses Dokument entbindet nicht von einer branchenüblichen Eingangskontrolle.
We do not guarantee that the product can be used for a special application.
This document does not release you from performing the standard control upon receipt of incoming goods.

SERVA Electrophoresis GmbH
Qualitätskontrolle/ Quality Control

Druckdatum/ printing date: 20.06.2023

Dr. Judith Koch

Daniela Lux-Helmstetter

Dieses Dokument ist ein Computerausdruck und deshalb ohne Unterschrift gültig.
This report has been computer generated and does not contain a signature.